

MOD 3000~9000TL3-X

- Max. efficiency 98.6%
- OLED and Touch button
- Type II SPD on DC and AC side
- String Monitoring
- AFCI optional



P O W E R
- I N G
T O M O -
R R O W



| Datasheet | MOD 3000TL3-X | MOD 4000TL3-X | MOD 5000TL3-X | MOD 6000TL3-X | MOD 7000TL3-X | MOD 8000TL3-X | MOD 9000TL3-X |
|-----------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
|-----------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|

Input data (DC)

| | | | | | | | |
|--|------------|-------|-------|-------|--------|--------|--------|
| Max. recommended PV power (for module STC) | 4500W | 6000W | 7500W | 9000W | 10500W | 12000W | 13500W |
| Max. DC voltage | 1100V | | | | | | |
| Start voltage | 200V | | | | | | |
| Nominal voltage | 580V | | | | | | |
| MPPT voltage range | 140V-1000V | | | | | | |
| No. of MPP trackers | 2 | | | | | | |
| No. of PV strings per MPP tracker | 1 | | | | | | |
| Max. input current per MPP tracker | 13A | | | | | | |
| Max. short-circuit current per MPP tracker | 16A | | | | | | |

Output data (AC)

| | | | | | | | |
|-----------------------------|---------------------------------|--------|--------|--------|--------|--------|--------|
| AC nominal power | 3000W | 4000W | 5000W | 6000W | 7000W | 8000W | 9000W |
| Max. AC apparent power | 3300VA | 4400VA | 5500VA | 6600VA | 7700VA | 8800VA | 9900VA |
| Nominal AC voltage (range*) | 220V/380V, 230V/400V (340-440V) | | | | | | |
| AC grid frequency (range*) | 50/60 Hz (45-55Hz/55-65 Hz) | | | | | | |
| Max. output current | 5.0A | 6.7A | 8.3A | 10.0A | 11.7A | 13.3A | 15.0A |
| Adjustable power factor | 0.8leading...0.8lagging | | | | | | |
| THDi | <3% | | | | | | |
| AC grid connection type | 3W+N+PE | | | | | | |

Efficiency

| | | | | | | | |
|---------------------|-------|-------|-------|-------|-------|-------|-------|
| MAX. efficiency | 98.3% | 98.3% | 98.3% | 98.3% | 98.6% | 98.6% | 98.6% |
| European efficiency | 97.5% | 97.5% | 97.5% | 97.5% | 98.1% | 98.1% | 98.1% |
| MPPT efficiency | 99.9% | | | | | | |

Protection devices

| | | | | | | | |
|----------------------------------|-------------------|--|--|--|--|--|--|
| DC reverse polarity protection | yes | | | | | | |
| DC Switch | yes | | | | | | |
| AC/DC surge protection | Type II / Type II | | | | | | |
| Insulation resistance monitoring | yes | | | | | | |
| AC short-circuit protection | yes | | | | | | |
| Ground fault monitoring | yes | | | | | | |
| Grid monitoring | yes | | | | | | |
| Anti-islanding protection | yes | | | | | | |
| Residual-current monitoring unit | yes | | | | | | |
| String fault monitoring | yes | | | | | | |
| AFCI protection | Optional | | | | | | |

General data

| | | | | | | | |
|---|---|---------------|---------------|---------------|---------------|---------------|---------------|
| Dimensions (W / H / D) | 425/387/138mm | 425/387/138mm | 425/387/138mm | 425/387/138mm | 425/387/178mm | 425/387/178mm | 425/387/178mm |
| Weight | 13.5kg | 13.5kg | 13.5kg | 13.5kg | 15kg | 15kg | 15kg |
| Operating temperature range | - 25°C ... +60°C | | | | | | |
| Noise emission (typical) | ≤35 dB(A) | | | | | | |
| Nighttime power consumption | < 1W | | | | | | |
| Topology | Transformerless | | | | | | |
| Cooling | Natural convection | | | | | | |
| Protection degree | IP66 | | | | | | |
| Relative humidity | 0-100% | | | | | | |
| Altitude | 4000m | | | | | | |
| DC connection | H4/MC4(Optional) | | | | | | |
| AC connection | Connector | | | | | | |
| Display | OLED+LED/WIFI+APP | | | | | | |
| Interfaces: USB/RS485/WIFI /GPRS/LAN/RF | yes/yes/Optional/Optional/Optional/Optional | | | | | | |
| Warranty: 5 / 10 years | Yes/Optional | | | | | | |

CE, VDE0126, Greece, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, N4105, TOR Erzeuger G98/G99, G100, AS4777, UNE217001, UNE206007, PO12.2

* The AC voltage range and frequency range may vary depending on specific country grid standard.
All specifications are subject to change without notice.